Declaration of Performance

VAP AL SK

1.	**Identification code**	VAP AL SK
2.	**Intended use**	Bitumen air and vapour control layers
3.	**Manufacturer**	IKO-AXTER, 6 rue Laferriere, 75009 PARIS, France www.axter.co.uk/downloads
4.	**Authorised representative**	N/A
5.	**System of assessment and verification of constancy of performance of the product**	System 3
6a.	**Product covered by the harmonised standard**	EN 13970 Declaration of the performance of the essential characteristics by the manufacturer
6b.	**European Technical Assessment**	N/A

7. Declared performance

Essential characteristics		Performance				Harmonised technical specification
		Value	Tolerance		Units	
			Min	Max		
Resistance to tearing (nail shank)	Longitudinal	150	50	-	N	EN 13970:2005/A1:2007
	Cross direction	150	50	-		
Tensile properties: maximum tensile force	Longitudinal	500	300	-	N/50mm	
	Cross direction	350	250	-		
Tensile properties: elongation	Longitudinal	15	5	-	%	
	Cross direction	40	15	-		
Watertightness under 2 kPa		Conform			-	
Water vapour transmission (new) EN 1931 (Sd)		≥1500			m	
Water vapour transmission (aged) EN 1296 (Sd)		≥1500			m	
Water vapour transmission (aged) EN 1847 (Sd)		NPD			m	
Reaction to fire		E			Class	
Dangerous substances		Note 1 and 2			-	

NA: Not applicable due to use of product.
NPD: No Performance Determined.
Note 1 : This product does not contain asbestos or tar constituents.
Note 2 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performance of the product identified above is in conformity with the set of declared performance/s. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer identified.

Only the most recent published version of this document is valid, available at www.axter.co.uk/downloads. Once downloaded, documents are uncontrolled so users should always ensure they are referring to the latest version. Further assistance is available from Axter Ltd's Technical Support Team, email: technical@axterltd.co.uk.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)



Paris
19/01/2024