

# Technical Data Sheet

---

## STARCOAT HYBRID CLEANER Liquid Waterproofing

**Starcoat Hybrid Cleaner is a transparent, fast-drying cleaner for use with Axter's Starcoat Hybrid liquid waterproofing system.**

Starcoat Hybrid Cleaner is designed for cleaning both the substrate prior to the installation of the Starcoat Hybrid liquid waterproofing system and to clean tools and non-polymerized stains.

## Characteristics

Properties	Unit	Value
Density	g/cm <sup>3</sup>	≈ 0.96

## Packaging

Starcoat Hybrid Cleaner is supplied in metal tins.

Product	Unit	Drum size
Quantity	L	5

## Colour

Starcoat Hybrid Cleaner is transparent.

## Storage and handling

Store product sealed in their original airtight container in a cool, dry and frost-free place.

Unopened tins have a shelf life of 36 months.

Keep the edges of the tin clean.

## Safety and risks

Please refer to the Safety Data Sheets (SDS) for the products used.

## General information

The above information, especially information about application of the products, is based on extensive development work, experience and is provided to the best of our knowledge. However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology or improvements to our products. Axter Ltd makes no warranties, express or implied, as to the properties and performance under any variations from such conditions in actual construction.

Axter Ltd reserves the right to modify and update this data at any time without prior notice. Only the latest version of this document is valid, available for download at [www.axter.co.uk/downloads](http://www.axter.co.uk/downloads). Once downloaded, documents are uncontrolled. Users should always confirm they are referring to the latest version prior to use. Further assistance is available from Axter Ltd's Technical Support Team, email: [technical@axterltd.co.uk](mailto:technical@axterltd.co.uk), telephone: 01473 935008.

The intended use of this product should be verified with Axter Ltd prior to adoption to ensure its suitability and compliance with specifications, project requirements, industry regulations, legislation, good practice, installation techniques and all other relevant guidance. Axter Ltd accepts no liability for non-compliant use of this product.