

CRX/30-18A



Max. load capacity
at wrist: 25/30 kg



Max. reach
(end of flange):
1889 mm

FANUC

Robot		Max. load capacity at wrist [kg]	Reach [mm] ^{(*)6}	Controlled axes	Repeatability [mm] ^{(*)4}	Mechanical weight [kg]	Motion range [°]						Maximum speed [mm/s] ^{(*)3}		Allowable Wrist Load ^{(*)5}			Input power source [VAC]	Protection	
Series	Version						J1	J2	J3	J4	J5	J6	Collaborative Mode	High Speed Mode	J4 Moment/ Inertia	J5 Moment/ Inertia	J6 Moment/ Inertia		Body standard	Wrist & J3 arm
CRX	A	30 25 ^{(*)1}	1756 1889 ^{(*)1}	6	±0.05	135	360	360	540	380	360	450	1000	2000	115.0 (100 ^{(*)2}) 4.7	85.0/ 4.00	32.0/ 2.00	200-240	IP67	IP67

● standard ○ on request - not available ^{(*)1} Operating space is expanded when 25kg payload mode is selected ^{(*)2} J4-axes allowable load moment when 25kg payload mode is selected ^{(*)3} Please set motion speed according to risk assessment of system. ^{(*)4} Based on ISO 9283 ^{(*)5} Nm/Kg.m² ^{(*)6} At the end of flange

CRX/30-18A

Standard model



CRX/30-18A

