

CRX/30-18A



Max. load capacity
at wrist: 25/30 kg



Max. reach
(end of flange):
1889 mm

FANUC

Robot		Max. load capacity at wrist [kg]	Reach [mm] ^(*)8)	Controlled axes	Repeatability [mm] ^(*)6)	Mechanical weight [kg]	Motion range [°]						Maximum speed [°/s] ^(*)5)		Allowable Wrist Load ^(*)7)			Input power source [VAC]	Protection	
Series	Version						J1	J2	J3	J4	J5	J6	Collaborative Mode [mm/sec]	High Speed Mode [mm/sec]	J4 Moment/ Inertia	J5 Moment/ Inertia	J6 Moment/ Inertia		Body standard	Wrist & J3 arm
CRX	A	30 25 ^(*)1) 40 ^(*)4)	1756 1889 ^(*)1) 1700 ^(*)2)	6	±0.05	135	360	360	540	380	360	450	1000	2000	115.0 (100 ^(*)3)) 4.7	85.0/ 4.00	32.0/ 2.00	200-240	IP67	IP67

● standard ○ on request - not available *1) Operating space is expanded when 25kg payload mode is selected *2) Operating space is limited when 40kg payload mode is selected *3) J4-axes allowable load moment when 25kg payload mode is selected *4) Max. load capacity when 40kg payload mode is selected. The wrist flange orientation is limited to downward-facing. *5) Please set motion speed according to risk assessment of system. *6) Based on ISO 9283 *7) Nm/Kg.m² *8) At the end of flange

CRX/30-18A

Standard model



CRX/30-18A

